

IN THE CLAIMS:

1(Currently Amended). An oven for cooking food, the oven comprising:

[[-]] an enclosure (2) for receiving the food to be heated and for containing a cooking atmosphere, the enclosure (2) comprising two horizontal walls forming respectively a bottom wall (9) and a top wall (10), interconnected by at least two vertical side walls (7,8), the enclosure (2) being closed by at least one door (5) that is likewise vertical, and communicating with the outside via an exhaust opening (28) for exhausting gas inside the enclosure (2) and at a pressure above atmospheric pressure; and

[[-]] a heater device (11) for heating the cooking atmosphere;

the oven being characterized by the fact that it comprises:

[[-]] a regulation chamber (33), filled at least in part with a liquid of volume adapted to vary between a high level and a low level, the regulation chamber (33) communicating with the enclosure via an air inlet (44); and

[[-]] an admission duct (45) which extends between a high end and a low end, the high end opening out outside the regulation chamber (33) and the enclosure (2), and the low end being closed by the liquid when the level of the liquid corresponds substantially to its high level.

2(Currently Amended). An oven according to claim 1, including an evacuation chamber (32) filled at least in part with a liquid of volume that is adapted to vary between a high level and a low level, said evacuation chamber (32) communicating with the regulation chamber (33).

3(Currently Amended). An oven according to claim 2, including an evacuation tube (38) extending between the exhaust opening (28) and a high end (39) opening out into the evacuation chamber (32) above the high and low liquid levels.

4(Currently Amended). An oven according to claim 3, including a chimney (40) extending between a first end (41) communicating with the outside of the evacuation chamber (32) and a second end (42) coming over the high level of the liquid, said second end allowing gas under positive pressure to escape from the enclosure (2) via the evacuation tube (38).

5(Currently Amended). An oven according to ~~any one of claims 2 to 4~~ claim 2, including a regulator (31) itself comprising the regulation chamber (33) and the evacuation chamber (32), these two chambers (32,33) constituting volumes that are separated from each other at least in part and that communicate with each other via a narrow passage (51) adapted to allow the liquid to flow between these two chambers (32,33).

6(Currently Amended). An oven according to ~~any one of claims 2 to 5~~ claim 2, including, in the evacuation chamber (32), a first temperature probe (46) for measuring the temperature of the gas coming from the exhaust opening (28), and in the regulation chamber (33), a second temperature probe (47) for measuring the temperature of the gas coming into the enclosure (2) via the air inlet (44).

7(Currently Amended). An oven according to ~~any one of claims 2 to 6~~ claim 2, comprising in the evacuation chamber (32), a first temperature probe (46) for measuring the temperature of the gas coming from the exhaust opening (28), and a second temperature probe (47) placed below the low level of the liquid in the evacuation chamber (32).

8(Currently Amended). An oven according to ~~claim 6 or claim 7~~, including calculation means (48) for determining the relative humidity in the oven (1) as a function of the temperatures measured by the first and second probes (46 and 47).

9(Currently Amended). An oven according to ~~any preceding~~ claim 1, including a fan (12) disposed inside the enclosure (2) to stir the cooking atmosphere heated by the heater device (11), said fan (12) creating a suction zone inside the enclosure (2), the air inlet (44) being situated substantially in the suction zone of the fan (12).

10(Currently Amended). An oven according to ~~any preceding~~ claim 1, including vapour-producing means (30) suitable for delivering water vapour into the enclosure (2).

11(Currently Amended). An oven according to ~~any preceding~~ claim 1, in which the exhaust opening (28) for exhausting gas under positive pressure inside the enclosure (2) is situated beneath the heater device (11).

12(Currently Amended). An oven according to ~~any preceding~~ claim 1, in which the exhaust opening (28) opens out substantially in the lowest point of the bottom wall (9).

13(Currently Amended). An oven according to ~~any preceding~~ claim 1, in which the exhaust opening (28) communicates with a siphon (29) adapted to evacuate liquids and condensates from the enclosure (2) while preventing cold air from rising into the enclosure (2).

14(Currently Amended). An oven ~~Oven~~ for cooking food, comprising:

[[-] an enclosure (2) for receiving the food to be heated and for containing a cooking atmosphere, this enclosure (2) comprising two horizontal walls (9,10), respectively forming a bottom wall (9) and a top wall (10), interconnected by at least two vertical side walls (8), this enclosure (2) being closed by at least one door (5) which is also vertical, and communicating with the outside by means of an evacuation aperture (28) for gases under positive pressure in the enclosure (2), characterised in that it comprises a first temperature probe (46) to measure the temperature of the gases issuing from the evacuation aperture (28).

15(Currently Amended). The oven according to claim 14, comprising calculating means (48) of calculating the humidity rates in the oven (1) as a function of the temperature measured at the first (46) probe.

16(Currently Amended). The oven according to claim 15, comprising a second temperature probe (47) to measure a reference temperature.

17(Currently Amended). The oven according to claim 16, wherein the humidity rates in the oven (1) is calculated by the calculating means (48) as a function of the temperature measured at the first (46) and second (47) probes.

18(Currently Amended). The oven according to ~~any one of claims 14 to 17~~ claim 14, comprising:

[[-]] a heater (11) for heating the cooking atmosphere,
[[-]] a fan (12), located in the interior of the enclosure (2), to stir the cooking atmosphere heated by the heater (11), this fan (12) creating an area of low pressure in the enclosure (2), and
[[-]] an air inlet (44) opening in the enclosure (2), approximately in said low-pressure area of the fan (12).

19(Currently Amended). The oven according to claim 18, comprising a regulation chamber (33), at least partially filled with a liquid of which the volume is adjusted so as to vary between a high level and a low level, this regulation chamber (33) communicating with the air inlet (44).

20(Currently Amended). The oven according to claim 19, comprising an admission duct (45) which extends between a high end and a low end, the high end opening outside the regulation chamber (33) and the enclosure (2), and the low end being covered by the liquid when the level of the liquid corresponds approximately to its high level.

21(Currently Amended). The oven according to ~~any one of claims 19 and 20~~ claim 19, comprising an evacuation chamber (32), at least partially filled with a liquid of volume adapted to vary between the high level and the low level, this evacuation chamber (32) communicating with the regulation chamber (33).

22(Currently Amended). The oven according to claim 21, comprising a regulator box (31), itself comprising the regulation chamber (33) and the evacuation chamber (32), these two chambers (33,32) constituting volumes which are at least partially separated from one another, communicating between one another by means of a narrow passage (51), adapted to allow the liquid to flow between these two chambers (32,33).

23(Currently Amended). The oven according to ~~any one of claims 21 and 22~~ claim 21, comprising an evacuation tube (38) extending between the evacuation aperture (28) and a high end (39), opening into the evacuation chamber (32) above the high and low levels of the liquid.

24(Currently Amended). The oven according to claim 23, comprising a chimney (40) extending between a first end (41) communicating with the outside of the evacuation chamber (32) and a second end (42) coming over the high level of the liquid, this second end (42) allowing the gases under positive pressure in the enclosure (2) to escape via the evacuation tube (38).

25(Currently Amended). The oven according to ~~any one of claims 22 to 24~~ claim 22, wherein the second temperature probe (47) is located beneath the low level of the liquid in the regulation box (31).

26(Currently Amended). The oven according to ~~any one of claims 21 to 25~~ claim 21, wherein the first temperature probe (46) is located above the high level of the liquid in the evacuation chamber (32).

27(Currently Amended). The oven according to ~~any one of claims 14 to 26~~ claim 14, comprising means for the production of steam (30), arranged to supply steam in the enclosure (2).

28-100(Canceled).